

RC-12 Data Sheet (terracotta heart)

DESCRIPTION: Mixture of very fine cocchiopesto, micronized aerial lime plus structuring component and beeswax. Formulated according to the original recipes, improved for the current quality of the raw materials, it must be applied by brush (soft or rough depending on the desired effect) obtaining colored surfaces in various degrees of transparency or coverage, satin, water-repellent but permeable to vapour.

Water repellency is enhanced by applying a coat of natural beeswax-based protectant.

USE: The product, whose origins are very ancient, is still made today following traditional processing methods. It is applied outdoors and indoors to obtain finishes of particular decorative and chromatic value. The glaze can be applied to all base plasters, preferably cocchiopesto or lime-based, ensuring excellent performance in adhesion, breathability and protection from atmospheric agents.

Avoid application on cement substrates, plaster plasters, substrates subject to efflorescence.

APPLICATION: Before installation, carefully clean the substrate from salts, mold, dust, oils, inconsistent or degraded parts. Saturate the substrate before application. Mix the mixture thoroughly by adding the liquid component and clean water (preferably distilled) and apply a first coat with a brush. The number of coats in application is at the discretion of the professional.

TECHNICAL DATA:

Grain size	Until 0 - 1 mm	Resistance to vapor diffusion	$\mu < 12$
Temperature of use	+5°C to +25°C	Storage and preservation	12 months, bound to the Intact storage and protected from sun and frost
Colors	As per folder		

WARNINGS:

- The package (bucket) must be closed with the original lid after each withdrawal.
 - Once hardened (carbonated) the product cannot be reused.
 - The packaged product is not afraid of frost.
 - Do not apply with temperatures below + 5°C and above + 25°C
- HERES, the manufacturer of the material, does not exercise any control over the applications, and does not assume responsibility for the use and installation methods followed.

SUPPLY AND ASSISTANCE: The product is supplied in a 9 + 2 kg jar to be added 4 liters of clean water. Technical staff is available to provide assistance and application courses.

N.B. The data given refer to generic tests and experiments and may be modified according to the conditions of installation. The user must in any case check the suitability of the product for the intended use, assuming all responsibility deriving from the use. Heres reserves the right to make technical changes without prior notice.

Agg.5/2024/Rev.02